









INDEX

CRANKSETS

Direct Mount Crankset /02 Road Bike Cranksets, Chainrings, /03 Pulley Wheels

TOOLSETS & TOOLS

BB Toolset 28.99 /04

BOTTOM BRACKET PARTS

T47 BB Sets |
For 85.5 BB Shell Width /06
For Spindle 24/28.99/30mm /07
Press-Fit BB Sets |
For Spindle 28.99mm /08
For Spindle 24mm/30mm /09
Eccentric BB Sets /10

HEADSETS

Tapered Headsets-Angle-Limited /11
Internal Cable Routing Headsets /12
Tapered Headsets /14
Semi-Integrated Headsets /16
Threaded Headsets /17
Threadless Headsets

Why are we the best in the BB, Headset, and Crankset business?

Because you get the most elegantly and precisely engineered bicycle components currently available, and because of this you will:

Keep your customers satisfied for longer —if you are a bike shop

Keep your bike(s) doing what you want them to reliably—and for longer—If you are an end user

38 Years Of Experience In The Bicycle Industry

How Do We Keep Your Customers Satisfied? Through Product Research, Development, and Innovation, continuously since 1984. On top of this RD&I foundation are the 4 pillars forming the key foci of our business.

Product Design

Give us your drawings or even a few ideas on a piece of paper. We'll bring your visualized product to fruition quickly and efficiently.

Manufacturing

We do most of our machining and assembly in house. Any outsourcing is only entrusted to workshops we've worked with for decades.

Material Selection

Our deep connections throughout Taiwan's complete supply chain enables us to find the right material at the right price.

Quality Of Product

Our rigorous QC regime creates components your customers will love, ensuring they'll be back for more when they finally need to.

We've Got You Covered

- 38 + Years Of Experience
- Precision Engineering
- Competitive Price
- Continuous Innovation









Registered to ISO 9001



Direct Mount Crankset -

Stronger and more Durable

TT1 (Direct Mount)

• Cranks: Forged AL6066

• Length: 165mm, 170mm, 172.5mm, 175mm

• Chainrings: 32^T, 34^T

• Spindle: Cr-Mo SCM440

• Speed: 12

• Chainline: 49mm / 52mm / 55mm

• Weight: $727g \pm 10g/175mm$ (BB Not Included)

TT2 (Direct Mount)

• Cranks: Forged AL6066

• Length: 165mm, 170mm, 172.5mm, 175mm

• Chainrings: 38^Tx24^T

• Spindle: Cr-Mo SCM440

• Speed: 12

• Chainline: 49mm

• Weight: $798g \pm 10g/175mm$ (BB Not Included)















KT1(4-Arm)-1X Gravel

• Cranks: Forged AL6066

• Length: 165mm, 170mm, 172.5mm, 175mm

• BCD: 110mm

Chainrings: 40^T, 42^T, 46^T

• Spindle: Cr-Mo SCM440

• Speed: 12

Chainline: 42mm

• Weight: 765g±10g/175mm (BB Not Included)







Accessories

Chainrings, Pulley Wheels



Y70A-6

A CONTRACTOR

Y70A-5

(13T)



Y70A-7

(15T)



Y75A-2

(14T) Narrow-Wide



TE

- Direct Mount (Narrow-Wide)
- Material: AL7075
- Teeth: 38^T
- Yamaha PW-X Compatible
- Weight: 112g (38^T)



R-TT1 (CL49)

- Direct Mount (Narrow-Wide)
- Material: AL7075
- Teeth: 32^T, 34^T
- Weight:77g (32^T)



(12T)

R-TT1 (CL52)

- Direct Mount (Narrow-Wide)
- Material: AL7075
- Teeth: 32^T, 34^T
- Weight:72g (32^T)



R-M9100

- Direct Mount (Narrow-Wide)
- Material: AL7075
- Teeth: 30^T~38^T
- Shimano Compatible
- Weight: 67g (32^T)



R-TC82

- BCD: 82mm (Narrow-Wide)
- Material: AL7075
- Teeth: 28^T, 30^T
- Weight: $53g (30^T)$



Toolsets & Tools



BB Toolset

Introducing the world's first toolset for SRAM's new DUB (28.99) bottom bracket and spindle standard. Removes 41, 42 & 46mm I.D. Press-Fit Bottom Brackets



- 12T
- Weight: 164g



- 16T
- Weight: 178g



- 12T & 24T • Weight: 182g



TOOL-PR3747

• Weight: 166g



- 12T & 16T
- Weight: 182g



TOOL-3747D

- Compatible with SRAM DUB BSA 24T & **DUB T47 16T**
- Weight: 170g

A05

BB Parts



DUB BB Sets 28.99





T47 BB Sets

For 85.5 BB Shell Width









C47-385P

C47-985

C47-385

- Available for spindle 30mm
- · Alloy Adapters & Sleeve
- Wrench (D47-392F) Included
- Weight: 177g
- C47-385E(W/O Sleeve)
- Available for spindle 30mm
- · Alloy Adapter & Nylon Sleeve
- Wrench (D47-392F) included
- Weight: 158g

- · Available for spindle 28.99mm
- · Alloy Adapters & Sleeve
- Wrench (D47-392F) Included
- Weight: 172g











D47-85

- · Available for spindle 24mm
- Alloy Adapter & Sleeve
- Wrench (D47-392F) included
- Weight: 142g

D47-85R

- · Available for spindle 24/22mm
- · Alloy Adapter & Sleeve
- Wrench (D47-392F) included
- Weight: 142g


C4785D

- · Available for spindle 28.99mm
- · Alloy Adapter & Sleeve
- Wrench (TOOL-3747D) included
- Weight: 120g



- Available for spindle 24mm
- · Alloy Adapter & Nylon Sleeve
- Wrench (D47-392F) included
- Weight: 123g





- Available for spindle 24/22mm • Alloy Adapter & Nylon Sleeve
- Wrench (D47-392F) included
- · Weight: 123g



C4785DP

- Available for spindle 28.99mm
- · Alloy Adapter & Nylon Sleeve
- Wrench (TOOL-3747D) included
- Weight: 102g



T47 BB Sets

For Spindle 24mm/28.99mm/30mm







T47-2977 (Asymmetrical)

- Available for BB shell width 77mm & spindle 28.99mm
- Alloy Adapter & Sleeve
- Wrench (M47-1216) included
- Weight: 132g

T47-3077 (Asymmetrical)

- Available for BB shell width 77mm & spindle 30mm
- Alloy Adapter & Sleeve
- Wrench (M47-1216) included
- Weight: 156g

R4729A

- Available for BB shell width 68/73mm & spindle 28.99mm
- Wrench (T30) Included
- Weight: 122g





- Available for BB shell width 77mm & spindle 24mm
- Alloy Adapter & Sleeve
- Wrench (M47-1216) included
- Weight: 164g



T47-2277 (Asymmetrical)

- Available for BB shell width 77mm & spindle 24/22mm
- Alloy Adapter & Sleeve
- Wrench (M47-1216) included

• Weight: 168g



T4734A

- Converter for T47 to BSA
- · Alloy Adapters
- Weight: 69g





Press-Fit BB Sets

For Spindle 28.99mm





R4129A

- For I.D. 41mm & Width 89.5/92mm BB Shell
- Two Wrenches (TOOL-FR1224) Included
- Weight: 147g





R4229A

- For I.D. 42mm & Width 73mm BB Shell
- Two Wrenches (T30) Included
- Weight: 145g





R4629A

- For I.D. 46mm & Width 73mm BB Shell
- Two Wrenches (T30) Included
- Weight: 162g





P4129A

- Available for BB Shell I.D.
 41mm & Width 89.5~92mm
- Steel Adapters & Alloy Sleeve
- Weight: 126g





P4229A

- Available for BB Shell
 I.D. 42mm & Width 73mm
- Alloy Adapter & Sleeve
- Weight: 116g





P4629A

- Available for BB ShellI.D. 46mm & Width 73mm
- · Alloy Adapters & Sleeve
- Weight: 126g



C4129AF (Fat Bike BB)

- Available for BB Shell
 I.D 41mm & Width 121mm
- For Spindle 28.99mm
- Weight: 138g



C4186D

- Available for BB shell
 I.D. 41mm & width 86.5mm
- Steel Adapter & Alloy Sleeve
- Weight: 112g



P46986

- Available for BB shell
 I.D. 46mm & width 86.5mm
- Alloy Adapter & Sleeve
- Weight: 117g



Press-Fit BB Sets

For Spindle 24mm/30mm







R4624A-R (SRAM)

R4630A

R4624A-S (Shimano)

- For BB Shell I.D. 46mm & Width 68~73mm
- · Alloy Adapters
- Weight: 145g

- For BB Shell I.D. 46mm & Width 68~73mm
- · Alloy Adapters
- Weight: 145g

- For BB Shell I.D 46mm & Width 68~86.5mm
- · Double Row Bearings
- Two Wrenches (D47-392F) Included
- Weight: 140g





P4624A-S (Shimano)

- For BB Shell I.D 46mm & Width 86.5mm
- · Thread-Fit
- Two Wrenches (D47-392F) Included
- · Weight: 143g



P4624A-R (SRAM)

- For BB Shell I.D 46mm & Width 86.5mm
- · Thread-Fit
- Two Wrenches (D47-392F) Included
- Weight: 143g











External BB Sets For Spindle 28.99mm

P3729A

- Available for 1.37"x 24T BB Shell & Width 68~73mm
- Wrench (TOOL-FR1224) Included
- Weight: 107g

C3729AF (Fat Bike BB)

- Available for 1.37" x 24T & BB Shell Width 100mm
- For Spindle 28.99mm
- Wrench (TOOL-FR1224) Included
- Weight: 104g



Eccentric BB set





P237SA

- For 1.37" x 24T & Width 68/73mm BB Shell)
- · Hexagonal Adapters for Bigger Range of Adjustment
- Tool-PR3747 Wrench Included
- Weight: 212g



R247SA

- For M47 x P1.0 & Width 68/73mm BB Shell)
- · Hexagonal Adapters for Bigger Range of Adjustment
- Tool-PR3747 Wrench Included
- Weight: 287g



C247D

- For M47 x P1.0 & Width 68/73mm BB Shell & spindle 28.99mm
- · Hexagonal Adapters for Bigger Range of Adjustment
- Tool-PR3747 Wrench Included
- Weight: 264g







- For BB Shell I.D. 54.5mm & Width 68mm
- Design for E-Bike
- Weight: 228g



P106A

- M47 X P1.0
- For BB Shell I.D. 60.3mm & Width 68mm
- Weight: 118g



G206A

- Eccentric BB for Tandem Bike
- I.D.46mm
- For BB Shell Width 86mm
- Weight: 125g



Tapered Headsets-Angle-Limited











- Alloy, Sealed Bearings
- 1-1/8" to 1.5"
- Tapered Head Tube& Steerer
- Angle-Limited

Dia Model	Top Nut	Bearing O.D.	Crown Cone	Height
P507A	1-1/8"	42/52	39.8	15.7





C307A-1 ZS44/28.6 | ZS56/40

- Alloy, Sealed Bearings
- 1-1/8" to 1.5"
- Tapered Head Tube & Steerer
- Angle-Limited

Dia	Top	Cup	Crown	Height
Model	Nut	O.D	Cone	
C307A-1	1-1/8"	44/56	39.8	17.8



C307A

ZS44/28.6 | ZS44/30

- Alloy Cap/Cup
- · Sealed Bearings
- Angle-Limited

Dia	Top	Cup	Crown	Height
Model	Nut	O.D	Cone	
C307A	1_1/8"	44	30	17.8



Internal Cable Routing Headsets



C522A

IS52/28.6 I IS52/40

- Alloy, Sealed Bearings
- 1-1/8" to 1.5"
- Tapered Steerer

Dia	Top	Bearing	Crown	Height
Model	Nut	O.D.	Cone	
C522A	1-1/8"	51.8	39.8	11.5



C525A

IS52/28.6 I IS52/40

- · Alloy, Sealed Bearings
- 1-1/8" to 1.5"
- · Tapered Steerer


Dia	Top	Bearing	Crown	Height
Model	Nut	O.D.	Cone	
C525A	1-1/8"	51.8	39.8	14



C522A-5

IS52/28.6 I ZS56/40

- · Alloy, Sealed Bearings
- 1-1/8" to 1.5"
- Tapered Head Tube & Steerer





C522A-1

IS52/28.6 I IS52/40

- Alloy, Sealed Bearings
- 1-1/8" to 1.5"
- Tapered Steerer

M	Dia lodel	Top Nut	Bearing O.D.	Crown Cone	Height
	C522A-1	1-1/8"	51.8	39.8	11.5



C522A-7

IS52/28.6 I IS60/45.8

- Alloy, Sealed Bearings
- 1-1/8" to 1.8"
- Tapered Head Tube & Steerer

Dia Model				
C522A-7	1-1/8"	51.8/60	45.8	11.5



C522A-2

IS52/28.6 I EC49/40

- Alloy, Sealed Bearings
- 1-1/8" to 1.5"
- · Tapered Steerer

Dia	Top	Cup	Crown	Height
Model	Nut	O.D	Cone	
C522A-2	1 1/8"	51.8/49.6	30.8	23.7



C522A-3

IS52/28.6 I IS52/40

- Alloy, Sealed Bearings
- 1-1/8" to 1.5"
- Tapered Steerer

Dia Model	Top Nut	Bearing O.D.	Crown Cone	Height
C522A-3	1-1/8"	51.8	39.8	11.5



C522A-8

IS52/28.6 I IS60/40

- Alloy, Sealed Bearings
- 1-1/8" to 1.5"
- Tapered Head Tube & Steerer

Dia	Top	Bearing	Crown	Height
Model	Nut	O.D.	Cone	
C522A-8	1-1/8"	51.8/60	39.8	11.5



Internal Cable Routing Headsets





INTERNAL CABLE ROUTING HEADSET WATERPROOF



C660A (waterproof)

ZS56/28.6 | ZS66/45.8

- Alloy, Sealed Bearings
- 1-1/8" to 1.8"
- Tapered Head Tube & Steerer

Model	a Top Nut	Cup O.D	Crown Cone	Height
C660A	1-1/8"	56/66	45.8	11.2



C550A (waterproof)

ZS56/28.6 | ZS56/40

- · Alloy, Sealed Bearings
- 1-1/8" to 1.5"
- · Tapered Steerer

Dia Model	Top Nut	Cup O.D	Crown Cone	Height
C550A	1-1/8"	56	39.8	11.5



C554A (waterproof)

ZS56/28.6 | ZS56/40

- Alloy, Sealed Bearings
- 1-1/8" to 1.5"
- Tapered Steerer
- Angle-Limited

Dia	Top	Cup	Crown	Height
Model	Nut	O.D	Cone	
C554A	1-1/8"	56	39.8	12.3



Tapered Headsets



D40F-7

IS42/28.6 | IS60/45.8

- · Alloy, Sealed Bearings
- 1-1/8" to 1.8"
- Tapered Head Tube
 & Steerer

Dia	Top	Bearing	Crown	Height
Model	Nut	O.D.	Cone	
D40F-7	1-1/8"	41.8/60	45.8	16.4



D40F-8

IS42/28.6 | IS60/40

- Alloy, Sealed Bearings
- 1-1/8" to 1.5"
- Tapered Head Tube & Steerer

Dia Model	Top Nut	Bearing O.D.	Crown Cone	Height
D40F-8	1-1/8"	41.8/60	39.8	16.4



P504A-1

IS42/28.6 I IS52/40

- · Alloy, Sealed Bearings
- 1-1/8" to 1.5"
- Tapered Head Tube & Steerer

Dia Model	Top Nut	Bearing O.D.	Crown Cone	Height
P504A-1	1-1/8"	41.8/52	39.8	5.4



C361A

IS52/28.6 I IS52/40

- · Alloy, Sealed Bearings
- 1-1/8" to 1.5"
- · Tapered Steerer

	FIRST
1	
	ALUMI NO



R520A

IS42/28.6 I IS52/40

- Alloy, Sealed Bearings
- 1-1/8" to 1.5"
- Tapered Head Tube& Steerer

Dia	Top	Bearing	Crown	
Model	Nut	O.D.	Cone	
R520A	1-1/8"	41.8/52	39.8	26.5-33.5



P506A

ZS44/28.6 I ZS56/40

- · Alloy, Sealed Bearings
- 1-1/8" to 1.5"
- Tapered Head Tube & Steerer

	Dia Model	Top Nut	Cup O.D	Crown Cone	Height
ı	P506A	1-1/8"	44/56	39.8	4.9



C566A-3

ZS44/28.6 | ZS66/45.8

- · Alloy, Sealed Bearings
- 1-1/8" to 1.8"
- Tapered Head Tube
 & Steerer

Dia Model	Top Nut	Cup O.D	Crown Cone	Height
C566A-3	1-1/8"	44/66	45.8	12



C566A-4

ZS44/28.6 | ZS66/40

- Alloy, Sealed Bearings
- 1-1/8" to 1.5"
- Tapered Head Tube
 & Steerer

Dia Model	Top Nut	Cup O.D	Crown Cone	Height
C566A-4	1-1/8"	44/66	30.8	12



P502A-344

ZS44/28.6 | EC44/40

- · Alloy, Sealed Bearings
- 1-1/8" to 1.5"
- · Tapered Steerer

Dia	Top	Cup	Crown	Height
Model	Nut	O.D	Cone	
P502A-344	1-1/8"	44	39.8	16



Tapered Headsets



CS3-5

ZS44/28.6 | EC44/40

- Steel, Ball Retainers
- 1-1/8" to 1.5"
- · Tapered Steerer

Dia Model	Top Nut	Cup O.D	Crown Cone	Height
CS3-5	1-1/8"	44	39.8	19.8



P506A-1

ZS44/28.6 | EC44/40

- · Alloy, Sealed Bearings
- 1-1/8" to 1.5"
- Tapered Steerer

Dia Model	Top Nut	Cup O.D	Crown Cone	Height
P506A-1	1-1/8"	44	39.8	14.9



C566A

ZS56/28.6 I ZS66/45.8

- Alloy, Sealed Bearings
- 1-1/8" to 1.8"
- Tapered Head Tube & Steerer

Dia	Top	Cup	Crown	Height
Model	Nut	O.D	Cone	
C566A	1-1/8"	56/66	45.8	11.2





PZ-502A

EC34/28.6 | ZS44/30

- Alloy, Sealed Bearings
- 1-1/8"
- Tapered Head Tube

Dia Model	Top Nut	Cup O.D	Crown Cone	Height
PZ-502A	1-1/8"	34/44	30	19.2



PZ-344A

EC34/28.6 | EC44/40

- Alloy, Sealed Bearings
- 1-1/8" to 1.5"
- Tapered Head Tube & Steerer

Dia Model	Top Nut	Cup O.D	Crown Cone	Height
P7-344A	1-1/8"	34/44	39.8	31



D510A-1

EC34/28.6 | EC44/40

- Alloy, Sealed Bearings
- 1-1/8" to 1.5"
- Tapered Head Tube & Steerer

Dia Model	Top Nut	Cup O.D	Crown Cone	Height
D510A-1	1-1/8"	34/44	39.8	28.2



Tapered Headsets



T571S

ZS44/28.6-26tpi I ZS56/40

- Alloy cap & Steel cups
- Ball Retainers
- 1-1/8" to 1.5"
- Tapered Head Tube & Steerer

Dia	Top	Cup	Crown	Height
Model	Nut	O.D	Cone	
T571S	25.4	44/56	39.8	18.9



C549A

ZS49/28.6 I EC49/40

- Alloy Cap/Cup
- Sealed Bearings
- 1-1/8" to 1.5"
- Tapered Steerer

	Dia Model	Top Nut	Cup O.D	Crown Cone	Height
-	C549A	1-1/8"	49.6	39.8	19.8



Semi-Integrated Headsets



DM-A1/A2/A4/A5

ZS55/28.6 | ZS55/40 ZS55/28.6 | ZS55/30 ZS56/28.6 | ZS56/40 ZS56/28.6 | ZS56/30

- · Alloy, Sealed Bearings
- ACB 45° x 45°

Dia Model	Top Nut	Cup O.D	Crown Cone	Height
DM-A1	1-1/8"	55	39.8	12.3
DM-A2	1-1/8"	55	30	12.3
DM-A4	1-1/8"	56	39.8	12.3
DM-A5	1-1/8"	56	30	12.3



DM-S1/S2/S4/S5

ZS55/28.6 | ZS55/40 ZS55/28.6 | ZS55/30 ZS56/28.6 | ZS56/40 ZS56/28.6 | ZS56/30

 Alloy Cap & Steel Cups Ball Retainers

Dia Model	Top Nut	Cup O.D	Crown Cone	Height
DM-S1	1-1/8"	55	39.8	13.1
DM-S2	1-1/8"	55	30	13.1
DM-S4	1-1/8"	56	39.8	13.1
DM-S5	1-1/8"	56	30	13.1





DM-S/DM-S3

ZS55/38.1 | ZS55/40 ZS56/38.1 | ZS56/40

• Alloy Cap & Steel Cups Ball Retainers

Dia Model	Top Nut	Cup O.D	Crown Cone	Height
DM-S	1.5"	55	39.8	13.1
DM-S3	1.5"	56	39.8	13.1



DM-A/DM-A3

ZS55/38.1 | ZS55/40 ZS56/38.1 | ZS56/40

- Alloy, Sealed Bearings
- ACB 45° x 45°

Dia Model	Top Nut	Cup O.D	Crown Cone	Height
DM-A	1.5"	55	39.8	12.3
DM _* Δ3	1.5"	56	39.8	12.3

Threaded **Headsets**



Threadless **Headsets**



Y90A EC29/25.4-24tpi I EC29/27 EC30/25.4-24tpi I EC30/26

- · Alloy Cap/Cup
- · Sealed Bearings



P701A EC29/25.4-24tpi | EC29/27 EC30/25.4-24tpi I EC30/26

- Alloy Cap & Cups, Steel Crown Race
- Sealed Bearings



HBI

EC34/28.6 | EC34/30

 Alloy Cap/Steel Cups & Crown Race

Crown Cone Height

- Cartridge Bearings
- Angle-Limited

Dia	Top	Cup	Crown	Height
Model	Nut	O.D	Cone	
Y90A	22.2	30/30.2	27/26.4	34.7

Dia	Top	Cup	Crown	Height
Model	Nut	O.D	Cone	
P701A	22.2	30/30.2	27/26.4	35.4


FIRST aseTA		FIRST ON
	= IRST out	
G508A		
	FIRST G508A	
(PST)		



Cranksets, BB Sets, Headsets, Tools, E-Bike Components Integrated & semi-integrated · threadless & threaded · tapered · isis drive & cartridge bb set · external bb set · press-fit bb set













FIRST Bicycle Components Co., Ltd.

45, Kung 9th Rd., Rinan Vil., Tachia Dist., Taichung, Taiwan (Tachia Industrial Zone) TEL: 886-4-26815039 FAX: 886-4-26815917 www.firstcomponents.com sales@firstcomponents.com