

Engineering Specifications 工程規格

方向燈組外型結構 External Structure of Turn Signal Lightset	• 長 度: 200mm	Length: 200mm
	• 材 質: PC環保、ABS、PA+纖	Material: eco-friendly PC, ABS, and PA + fiber glass
LED	• E5 3W x 3 Hi-Power-White	E5 3W x 3 Hi-Power-White
	• 色 度: X=0.3206, Y=0.3301	Color Test: X=0.3206, Y=0.3301
	• 光 度: 928CD	Luminosity: 928CD
無線遙控IC Wireless Controlling IC	• 電 壓: 1.9V~3.6V	Voltage: 1.9V~3.6V
	• 頻 率: 2400~2527mhz	Frequency: 2400~2527mhz
	• 遙控距離: > 12m	Effective Controlling Distance: > 12m
速度表 Speed Meter	• 頻率: RF/單一製程密碼	Frequency: RF/exclusive code
	• IC: 磁感應霍爾	Magnetic Hall IC
	• 電 壓: 3.6V~5.0V	Voltage: 3.6V~5.0V
LCD	• 電 壓: 3.3V	Voltage: 3.3V
	• 背光板: 白光穿透顯示背光板	Backlight: White light penetrates from the backlight
充電式鋰電池 Rechargeable Lithium Battery	• 前 燈: 3.7V-4400mah	Front Light: 3.7V-4400mah
	• 後 燈: 3.7V-1000mah	Rear Light: 3.7V-1000mah
	• 厚 度: 7.7mm	Thickness: 7.7mm
	• 長 度: 83mm	Length: 83mm
	• 寬 度: 37mm	Width: 37mm
光敏控制器 Auto-Sensitive Sensor	• 電 壓 (Vdc): 100vdc	Voltage (Vdc): 100vdc
	• 額定功率 (mW): > 50mW	Power (mW): > 50mW
	• 環境溫度 (度): -30~+50°C	Ambient Temperature (degree): -30~+50°C
	• 明電阻: 20~50 (KΩ)	KΩ: 20~50
	• 暗電阻: > 1 (MΩ)	MΩ: > 1
坡度表 Gradient Indicator	• 陀螺儀 IC	Gyroscope IC
	• 功 率: ± 500 ± 110	Power: ± 500 ± 110
	• 電 壓: -0.3V to 5.0V	Voltage: -0.3V to 5.0V
	• 額 定: ± 90	Rated Value: ± 90